

Aurora AIC-PB8F-L Bullet Network Camera



High-Level 8MP Fixed Bullet with I-IR

- ▶ Exceptional image in 4K
- ▶ Perimeter guard included : line crossing, Intrusion, Entrance & Region Detection
- ▶ Classifies humans and vehicles to decrease false alarms
- ▶ Face Recognition
- ▶ Advance People counter
- ▶ Aurora Light and Up to 120 dB Optical WDR (Wide Dynamic Range)
- ▶ I-IR up to 30m IR distance



SPECIFICATIONS

CAMERA

Image Sensor

- 1/2.7", progressive scan, CMOS

Lens

- 4.0 mm, F1.6, Fixed Iris
- Horizontal field of view: 86°
- Vertical field of view: 44°
- Diameter field of view: 112°

Day / Night

- IR-cut filter with auto switch (ICR)

Minimum Illumination

- Color: 0.005 Lux, B/W: 0 Lux : F 1.6

Shutter Time

- Auto/Manual, 1 ~ 1/100000s

VIDEO

Video Compression

- H.265, H.264, MJPEG

Resolutions

- 3840*2160 , 8MP

Image Settings

- White Balance, Digital noise reduction, Intelligent IR (I-IR), Flip, Defog, HLC, BLC, Corridor mode, WDR 120dB, Privacy mask Up to 4 areas, up to 8 Overlay

Video Streaming

- Triple streams

Frame Rate

- M-Stream: 8MP (3840*2160), Max 20fps; 5MP (3072*1728), Max 30fps; 4MP (2560*1440), Max 30fps; 1080P (1920*1080), Max 30fps
- Sub-Stream: 1080P (1920*1080), Max 30fps; 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360, Max 30fps
- 3rd-Stream: D1 (720*576), Max 30fps; 640*360, Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps

NETWORK

Security

- Password protection, strong password, HTTPS encryption, Export operation logs, basic and digest authentication for RTSP, digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF

Compatible Integration

- ONVIF (Profile S, Profile G, Profile T), API, SDK

Supported Protocols

- IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSL/TLS, SSH

SYSTEM INTEGRATION

Analytics

- Aurora Perimeter guard included : line crossing, Intrusion, Entrance & Region Detection, Face Recognition, Aurora advance People counter

Events

- Motion detection, Audio detection, Tampering Alarm, Watermark, IP Address Filtering, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication

GENERAL

Protection Certificate

- IP67 (IEC 60529-2013)

Power

- DC12V±10% , PoE+ (IEEE802.3 at), Power consumption: Max 6.0W

Connectors

- 1 * Built-in microphone , Network: 1* RJ45, 10M/100M Base-TX Ethernet
- Power: Ø 5.5mm coaxial power plug

Storage

- Support : Micro SD, up to 256 GB, ANR, NAS (NFS)

Operating Conditions

- -30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)

Storage Conditions

- -30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)

Housing Material

- Metal

Approvals

- EMC: EN 55032:2015; EN 55024:2010; EN 61000-3-2:2014; EN 61000-3-3:2013; FCC CFR 47 Part 15
- IEC 62368-1; EN 62368-1; UL 62368-1
- CE-ROHS (2011/65/EU; (EU)2015/863); WEEE (2012/19/EU); REACH (Regulation (EC) No 1907/2006)

Dimensions (L * W * H)

- 156 * 63 * 63mm

Weight

- 0.41kg

Included Accessories

- User manual, 1 Sets Screws; HEX key; Drilling template; Bracket adapter; Plug, ...

Video Management Software

- AuroraStation, AuroraLive, AuroraView

Warranty

- Aurora 3-year warranty, Check www.Auroratec.ca/warranty