

## Server Pro

---

Heavy Duty with unbeatable weight capacity, High flexibility in equipment installation. Ultra-tough structure and high load capacity. Unique structure design. Various air flow choices on front, back and side doors. Wide selection of accessories. Blank, gland or brush cable entry on top and bottom. Adjustable foot, casters or plinth option for bottom. Value cost effective solution for Server rooms, Data Centers, Office, Branches, Residential complexes, educational and commercial locations. Fully assemble Available in range of size variants.



- ▶ Enforced front door with three-point lock
- ▶ 19" standard installation with Various accessories
- ▶ Removable side panels and Assembled frame structure
- ▶ Leveling feet and heavy-duty castors
- ▶ Several lockable cable entries on top and bottom
- ▶ Front and rear door easy to install, remove and reverse
- ▶ Bottom ventilation and rat proof
- ▶ Load capacity: Static load 1500 KG


## Chart Size

PART NUMBER	HEIGHT (mm)	WIDTH (mm)	DEPTH (mm)	RACK UNIT	Product Type
AIR-32-2323-S	1575	600	600	32	Server Pro
AIR-32-2331-S	1575	600	800	32	Server Pro
AIR-32-2339-S	1575	600	1000	32	Server Pro
AIR-38-2323-S	1830	600	600	38	Server Pro
AIR-38-2331-S	1830	600	800	38	Server Pro
AIR-38-2339-S	1830	600	1000	38	Server Pro
AIR-38-3139-S	1830	800	1000	38	Server Pro
AIR-42-2323-S	2020	600	600	42	Server Pro
AIR-42-2331-S	2020	600	800	42	Server Pro
AIR-42-2339-S	2020	600	1000	42	Server Pro
AIR-42-2343-S	2020	600	1100	42	Server Pro
AIR-42-2347-S	2020	600	1200	42	Server Pro
AIR-42-3139-S	2020	800	1000	42	Server Pro
AIR-42-3143-S	2020	800	1100	42	Server Pro
AIR-42-3147-S	2020	800	1200	42	Server Pro
AIR-48-2323-S	2285	600	600	48	Server Pro
AIR-48-2331-S	2285	600	800	48	Server Pro
AIR-48-2339-S	2285	600	1000	48	Server Pro
AIR-48-3139-S	2285	800	1000	48	Server Pro
AIR-48-3143-S	2285	800	1100	48	Server Pro
AIR-48-3147-S	2285	800	1200	48	Server Pro

## Door Options

---

- Tempered Glass door
- Plexi Glass door
- Perforated door
- Louver door
- Solid door
- Double perforated door



## Cabinet Roof

---

- 4 cable entry space can be used directly or with brush, Foam or other entry accessories
- 4 preconfigured fans

## Fan Module

---

- Pre configured fan module with 4 fans
- Installed on cabinet top removable module

## Moving in depth

---

- Adjustable 19 inch rails in depth in every 4/1 inch (11.1125 mm)
- pre configured cable tray in middle

## 19 inch rails

---

- Standard 19 inch punches compatible with all standard 19 inch rackmount devices
  - punches for M6 cage nuts
  - Silkscreen printed unit numbers

## Back door

---

- Perforated double back door 3 point locking system available options: removable panel, louver panel, plexi glass, door, tempered glass door single perforated door

## Side Panels

---

- Dual separated side panels on each side
- Lockable sliding latch

## Floor

---

- Heavy duty casters
- Leveling feet
- Adjustable floor mount adapter

## Door lock

---

- Standard 3 point locking system to ensure
- secure door locking Multi point locking system available

## Direct weight control

---

- addition to standard structure on wide cabinets to reach maximum weight capacity