

Aurora AINS-DS08T-F Intercom Systems

8" IPS LCD Capacitive Touch Screen

- ▶ 3 output relays for door locks
- ▶ Camera: 120° wide-angle 2MP HD camera with automatic lighting
- ▶ Support WDR technology to lighten the dark areas and darken the overexposed parts of the image
- ▶ Door entry methods: call, face, IC card (13.56MHz), ID card (125kHz), PIN code, APP, Bluetooth
- ▶ Anti-spoofing algorithm against photos and videos
- ▶ Support 10,000 faces, and 100,000 cards
- ▶ IP / IK Rating: IP65, IK08
- ▶ Tamper alarm
- ▶ Installation: Flush Mount
- ▶ Easy integration with other SIP devices by SIP 2.0 protocol



SPECIFICATIONS

Display

- Display: 8-inch IPS LCD
- Resolution: 1280 x 800

Audio

- Audio Codec: G.711
- Echo Cancellation
- DTMF: RFC2833
- Microphone: Built-in microphone
- Speaker: 8Ω / 1W

Networking

- Protocol: ONVIF, SIP, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP

Video

- Video Codec: H.264
- Video Resolution: up to 1920 x 1080
- Viewing Angle: 120°(H) / 75°(V) / 131°(D)
- Max. Image Transfer Rate: 1080p - 25fps
- Light Compensation: LED white light

FEATURES

PHYSICAL

- System: Android
- RAM: 2 GB
- ROM: 8 GB
- Front Panel: Aluminum
- Power Supply: PoE+ (802.3at) or DC 12V/3A
- Standby Power: 8 W
- Rated Power: 16 W
- Camera: 2MP, CMOS, WDR
- IR Sensor: Support
- Wiegand Port: Support
- Ethernet Port: 1 x RJ45, 10/100 Mbps adaptive
- Door Entry: Face, IC (13.56MHz) & ID (125kHz) card, PIN code, Bluetooth
- Reset Button: 1
- RS485 Port: 1
- Relay Out: 3
- Input: 4
- IP / IK Rating: IP65 / IK08
- Installation: Flush Mounting
- Surface Mounting DIM: 140 x 300 x 60.3 mm
- Working Temperature: -40°C to +55°C
- Storage Temperature: -40°C to +70°C
- Working Humidity: 10% to 90% (non-condensing)