

Aurora AINS-DS34S-F Intercom Systems

4.3" SIP Video Door Phone

- ▶ Front panel: Aluminum + Tempered Glass
- ▶ Display: 4.3 Inch, color TFT LCD
- ▶ Camera: 2 Mega pixels, automatic lighting, 110°(H) / 67°(V)
- ▶ RF card reader: 13.56MHZ & 125kHz
- ▶ Output Relay: 3 output relay for door opener
- ▶ IP / IK Rating: IP65, IK06
- ▶ Installation: Flush Mount
- ▶ PoE (IEEE802.3af, Power-over-Ethernet)
- ▶ Built-in Induction loop



SPECIFICATIONS

Display

- Display: 4.3-inch TFT LCD
- Resolution: 480 x 272

Audio

- Audio Codec: G.711
- Echo Cancellation
- DTMF: RFC2833
- Microphone: Built-in microphone
- Speaker: 8Ω / 1W

Networking

- Protocol: ONVIF, SIP, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP

Video

- Video Codec: H.264
- Video Resolution: 1280 x 720
- Viewing Angle: 110°(H) / 67°(V) / 127°(D)
- Max. Image Transfer Rate: 720p – 25fps
- Light Compensation: LED white light

FEATURES

PHYSICAL

- System: Linux
- Front Panel: Aluminum
- Button: Mechanical
- Power Supply: PoE (802.3af) or DC 12V/2A
- Standby Power: 1.5 W
- Rated Power: 9 W
- Camera: 2MP, CMOS
- IR Sensor: Support
- Wiegand Port: Support
- Ethernet Port: 1 x RJ45, 10/100 Mbps adaptive
- Door Entry: IC (13.56MHz) & ID (125kHz) card, PIN code
- Reset Button: 1
- RS485 Port: 1
- Relay Out: 3
- Input: 4
- IP / IK Rating: IP65 / IK07
- Installation: Flush Mounting
- Flush Mounting DIM: 295 x 133 x 63.5 mm
- Working Temperature: -40°C to +55°C
- Storage Temperature: -40°C to +70°C
- Working Humidity: 10% to 90% (non-condensing)