

# Aurora AINS-IM07L Intercom Systems

---

## SIP Indoor Monitor (Linux Version) 7"

- ▶ 7" TFT capacitive touch screen, 1024 x 600
- ▶ Two-way communication based on SIP v2.0 protocol
- ▶ Powered by PoE or external source
- ▶ WIFI & TF card



## SPECIFICATIONS

## FEATURES

### Display

- Display: 7-inch TFT LCD
- Screen: Capacitive touch screen
- Resolution: 1024 x 600

### Networking

- Protocol: ONVIF, SIP, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP

### Audio

- Audio Codec: G.711
- Echo Cancellation
- DTMF: RFC2833
- Microphone: Built-in microphone
- Speaker: 8Ω / 1W

### Video

- Video Codec: H.264

## PHYSICAL

---

- System: Linux
- RAM: 128 MB
- ROM: 128 MB
- Front Panel: Plastic
- Power Supply: PoE (802.3af) or DC 12V/2A
- Standby Power: 2 W
- Rated Power: 9 W
- Wi-Fi: IEEE802.11 b/g/n,@2.4GHz
- Ethernet Port: 1 x RJ45, 10/100 Mbps adaptive
- TF Card Slot: 1
- RS485: 1
- Power Output: 1 (12V/100mA)
- Doorbell Input: 8 (use any alarm input port)
- Alarm Input: 8
- Installation: Surface Mounting / Desktop
- Dimension: 195 x 130 x 14.5 mm
- Working Temperature: -10°C to +55°C
- Storage Temperature: -40°C to +70°C
- Working Humidity: 10% to 90% (non-condensing)